







Component

					
Tin Interface 8 Units	ER-IC-ST30B/G 6 Units	ER-EC-ST30B 4 Units	ER-SP-ELT/BA 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 8 pcs
PV-ezRack, SolarRoof Kit of Tin Roof for 4 Panels with 30 mm Clamps with Grounding Pins, Black Anodized Part No.: K-SR-05/4/30/G/BA (bar code: 21-136-00048)					

					
Tin Interface 14 Units	ER-IC-ST30B/G 14 Units	ER-EC-ST30B 4 Units	ER-SP-ELT/BA 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 16 pcs
PV-ezRack, SolarRoof Kit of Tin Roof for 8 Panels with 30 mm Clamps with Grounding Pins, Black Anodized Part No.: K-SR-05/8/30/G/BA (bar code: 21-136-00049)					

					
ER-I-01/CS 8 Units	ER-IC-ST30B/G 6 Units	ER-EC-ST30B 4 Units	ER-SP-ELT/BA 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 8 pcs
PV-ezRack, SolarRoof Kit of Tile roof for 4 Panels with 30 mm Clamps with Grounding Pins, Black Anodized Part No.: K-SR-01/4/30/G/BA (bar code: 21-137-00033)					

					
ER-I-01/CS 14 Units	ER-IC-ST30B/G 14 Units	ER-EC-ST30B 4 Units	ER-SP-ELT/BA 2 Units	EZ-GL-ST 2 Units	EZ-CC-PV/2 16 pcs
PV-ezRack, SolarRoof Kit of Tile roof for 8 panels with 30 mm Clamps with Grounding Pins, Black Anodized Part No.: K-SR-01/8/30/G/BA (bar code: 21-137-00034)					

Technical Specification

Roof type	K-SR-05/4/30/G/BA & K-SR-05/8/30/G/BA : Tin Roof K-SR-01/4/30/G/BA & K-SR-01/8/30/G/BA : Tile Roof
Purlin requirement	Metal or Timber purlin
Screw specification	K-SR-05/4/30/G/BA & K-SR-05/8/30/G/BA : Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-SR-01/4/30/G/BA & K-SR-01/8/30/G/BA : Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips screw
PV panel dimension	Framed PV Modules of 30 mm in height
Weight	K-SR-05/4/30/G/BA : 1.915 Kg K-SR-05/8/30/G/BA : 3.217 Kg K-SR-01/4/30/G/BA : 5.755 Kg K-SR-01/8/30/G/BA : 9.937 Kg
Packaging	K-SR-05/4/30/G/BA : 1 unit per pack ;8 packs (8 units) per carton K-SR-05/8/30/G/BA : 1 unit per pack ;4 packs (4 units) per carton K-SR-01/4/30/G/BA : 1 unit per pack ;2 packs (2 units) per carton K-SR-01/8/30/G/BA : 1 unit per pack ;1 packs (1 units) per carton
Material	Tin Interface : AL6005-T5 Tile Interface : Q345B Cable Clip : SUS304(3/4H) Grounding Lug : SUS316&AL6005-T5 Clamp and Splice : AL6005-T5
Finish and Color	Black Anodized Silver Hot Dip Galvanized (Tile Interface)
Standard	AS NZS1170.2-2021