

Kit for SolarRoof for 4 Panels with 30mm Clamps with Grounding Pins

Component

					
ER-I-05 8 Units	ER-IC-ST30/G 6 Units	ER-EC-ST30 4 Units	ER-SP-ECO 2 Units	EZ-GL-AT 2 Units	EZ-CC-PV/2 8 Units
Kit for SolarRoof Tin Roof for 4 Panels with 30mm Clamps with Grounding Pins Part No.: K-SR-05/4/30/G (bar code: 21-136-00045)					

					
ER-I-01/CS 8 Units	ER-IC-ST30/G 6 Units	ER-EC-ST30 4 Units	ER-SP-ECO 2 Units	EZ-GL-AT 2 Units	EZ-CC-PV/2 8 Units
Kit for SolarRoof Tile Roof for 4 Panels with 30mm Clamps with Grounding Pins Part No.: K-SR-01/4/30/G (bar code: 21-137-00030)					

Technical Specification

Application	K-SR-05/4/30/G: Tin Roof K-SR-01/4/30/G : Tile Roof
Purlin Requirement	K-SR-05/4/30/G: Metal or Timber purlin K-SR-01/4/30/G : Timber rafter
Screw Specification	K-SR-05/4/30/G: Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-SR-01/4/30/G : Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips screw
PV panel dimension	Framed PV Modules of 30 mm in height
Weight	K-SR-05/4/30/G: 2.254 Kg K-SR-01/4/30/G : 5.926 Kg
Packaging	K-SR-05/4/30/G: 1 unit per pack ;8 packs (8 units) per carton K-SR-01/4/30/G: 1 unit per pack ;2 packs (2 units) per carton
Material	Tin Interface: AL6005-T5 Tile Interface: Q345B Cable Clip: SUS304(3/4H) Grounding Lug: SUS316&AL6005-T5 Clamp and Splice: AL6005-T5
Finish and Color	Silver Anodized (Fabricated Surfaces are Mill Finish) Hot Dip Galvanized (Tile Interface)
Standard	AS NZS1170.2-2021